






ASG Ø600




Back view




Front view



Section view A-A



ASG-G HDPE/SS316 Penstock Specification



Opening: Ø600mm
 Standard supplied with a non-rising spindle.
 It has an HDPE back plate.
 EPDM lip seal between door and frame plate.
 Supplied with neoprene seal between wall and frame plate.
 Door made from HDPE and large penstocks will be reinforced with SS316 U-profiels.

Materials used; HDPE, SS316, EPDM, POM, Neoprene.
 Max. load (on/off seating):
 5 MWC from bottom invert level (B.I.L.)
 Bare shaft: Ø20mm
 All dimensions in mm

Please refer to our installation manual for more detailed information regarding mounting

Ca = Chemical anchors (incl. capsule)
 (8x) M10x165 - A4

(Threaded rod+washer+nut)

Wa = Wedge anchors
 (8x) M10x60 - A4

(Expansion clip+Countersunk bolt)

Signed for agreement: Name: Date:.....

The stated sizes are approximate. We advise you to measure the materials immediately after delivery before you proceed to installation!
 Copyright: This drawing remains property of Aquafix Milieu B.V. Nothing of this may be reproduced or multiplied without the permission of Aquafix Milieu B.V.

AQUAFIX MILIEU

Postbus 288 3640 AG Mijdrecht
 T: +31 (0)297 - 26 29 29
 F: +31 (0)297 - 26 12 72
 E: info@aquafix.nl
 W: www.aquafix.nl

Get.: GC Datum: 07-08-2020

Penstock ASG Ø600 - HDPE/SS316			Rev.:1
Model: Wallmount (G) - Non-rising spindle			
Artikelnr.: 670ASG0600G			
			± 72 kg.
Schaal: 1:11	Formaat: A3	Tek. nr.: ASG1900149	Blad:9